



# COMBAT®

## PORTABLE FIRE EXTINGUISHERS

### HALOTRON™ I STORE FRESSURE EXTINGUISHER

#### Green Colour Band

Approved To BSEN3

- Replacement of Halon 1211 / Carbon Dioxide Fire Extinguisher
- Clean Extinguishing Agent
- Effective Suppression for Class A, B, C & E Fires
- Use In Clean Environment
- Widely used in Offices, Clean Rooms, M&E Rooms, and Server Rooms etc.
- Light Weight
- Hight Performance
- Signal Red (RAL3000) Epoxy Polyester Power

### CARBON DIOXIDE EXTINGUISHER

#### Black Colour band

Approved to BSEN3

- Compile to AS/NZS 1841:1997
- Effective Suppression for Class B, C & E Fires
- Non-Conductive of Electricity
- High Pressure Hardware
- Signal Red (RAL 3000) Epoxy Polyester Power Coating



Model	C-2CSEC	C-5CSEC	C-2HSE	C-4HSE	C-6HSE
Capacity (kg)	2.0	5.0	2.0	4.0	6.0
Extinguishing Medium	Carbon Dioxide		Halotron™ I		
Propellant Type	Carbon Dioxide		Argon		
Fire Rating	21B	55b	5A/34B	8A/55B	13A/70B
Class of Fire	B, C & Electrical		A, B, C & Electrical		
Test pressure	250 bar		22.5 bar		
Max. Working Pressure	60 Kg/cm <sup>2</sup>		6.9 Kg/cm <sup>2</sup>	8.63 Kg/cm <sup>2</sup>	8.63 Kg/cm <sup>2</sup>
Overall Height (mm)	522	670	460	484	525
Diameter (mm)	114	152	98	150	190
Empty Weight (kg)	Refer to cylinder		1.84	2.76	3.47
Full Weight (kg)±	8.08	18.12	3.84	6.76	9.47
Min. Discharge Time (Sec)	10	12	6.1	9.2	9.4
Min. Discharge Range (M)	2	2	3	5	5
Approved by PSB	✓	✓	✓	✓	✓

The company reserves the right to change the specification without prior notice.

### GENERAL INFORMATION

Operating Temperature Range	Safe Operating Distance
20 <sup>0</sup> C to +60 <sup>0</sup> C	2 meter

**COMBAT®**