

Dry Powder Fire Extinguishers



Stored Pressure Mobile

Features:

- Ready for instant use and simple to operate.
- Fully controlled and easy operation by rust free brass valve.
- Cart and cylinder are made of rugged steel and welded to meet extreme use conditions.
- Easily transportable.
- Highly visible pressure-indicating gauge.
- Electrostatic powder painting after shot blasting ensures maximum corrosion resistance.

Options

- For three wheels, suffix "S"
- Other hose lengths available upon request

Model	NTDP25	NTDP30	NTDP50	NTDP75	NTDP100	NTDP150
Extinguisher Capacity	25Kg	30Kg	50Kg	75Kg	100Kg	150Kg
Working Pressure	15Bar					
Test Pressure	30Bar					
Total Weight	59.5Kg	76Kg	100Kg	127.5Kg	180.7Kg	239Kg
Range of Discharge	7-9m	7-9m	7-9m	7-9m	8-9m	8-9m
Duration of Discharge	25-30 Sec	30-35 Sec	40-45 Sec	65-70 Sec	85-90 Sec	135-140 Sec
Operating Temperature	-20°C to +60°C					
Hose Length	3m	3m	5m	7m	7m	7m

Dry Powder Fire Extinguishers



External CO₂ Cartridge Mobile

Features:

- Ready for instant use and simple to operate.
- Fully controlled and easy operation by rust free brass valve.
- Cart and cylinder are made of rugged steel and welded to meet extreme use conditions.
- Easily transportable.
- Incorporated with high pressure external CO₂ cartridge.
- Electrostatic powder painting after shot blasting ensures maximum corrosion resistance.

Applications

NAFFCO Mobile Fire Extinguishers are manufactured to provide protection for hazardous areas where the potential for large fire exists.

Typical applications include: Paint Spray Booths, Dip and Quench Tanks, Offshore Platforms, Loading Racks, Fuel Storage Areas, Airports, and Heavy Manufacturing Operations.

Options

- Special NTDP-C-M series with metal dry powder for class D fire of Magnesium, Sodium etc.
- Special PVC internal coating.

Model	NTDPC25	NTDPC30	NTDPC50
Extinguisher Capacity	25Kg	30Kg	50Kg
Working Pressure	15Bar		
Test Pressure	30Bar		
Total Weight	68Kg	73Kg	105Kg
Range of Discharge	7-9m	7-9m	7-9m
Duration of Discharge	25-30 Sec	30-35 Sec	40-45 Sec
Operating Temperature	-20°C to +60°C		
Hose Length	3m	3m	5m