

Dry Powder Fire Extinguishers



Stored Pressure Portable

Features:

- Ready for instant use.
- Highly effective on class A, B, C & E fire.
- Heavy duty steel cylinder.
- Made of special CRCA sheet with Argon/CO₂ welding process.
- Simple operation and maintenance.
- Cylinders are 100 % factory tested to 30 bar.
- Easy grip valve for comfortable operation.
- Nickel plated Brass Valve with reliability and long life.
- Rugged PVC pick up tube enables smooth flow of the agent.
- Precision built mechanical pressure gauge.
- Electrostatic powder painting after shot blasting, ensures maximum corrosion resistance.
- Plastic Base is available upon request.

Applications

NAFFCO dry chemical extinguishers are designed for the protection of light, ordinary and extra high hazards.

These compact extinguishers are suited for both industrial and commercial fire protection needs.

Typical applications include:
Light Manufacturing,
Warehouses, Restaurants,
Office Buildings, Shop Areas,
Auto Repair Shops, Paint
Process Areas, Welding
Areas, Machinery,
Residential Apartments,
Parking Garages, Aircraft
Servicing Areas, Material
Handling Vehicles, and
many others.

Model	NP1	NP2	NP5L	NP4.5	NP6	NP10	NP12
Extinguisher Capacity	1Kg	2Kg	5Lbs	4.5Kg	6Kg	10Kg	12Kg
Working Pressure	14Bar	14Bar	14Bar	15Bar	15Bar	15Bar	15Bar
Test Pressure	30Bar						
Total Weight	1.8Kg	3.7Kg	4Kg	7.3Kg	9.5Kg	14Kg	16.7Kg
Range of Discharge	4-5m	5-7m	5-7m	6-8m	6-8m	6-8m	6-8m
Duration of Discharge	7-9Sec	8-10Sec	9-11Sec	10-12Sec	14-16Sec	16-18Sec	18-22 Sec
Operating Temperature	-20°C to +60°C						

Dry Powder Fire Extinguishers



External CO₂ Cartridge Portable

Features:

- Rugged, durable, reliable fire protection.
- Highly effective on class A, B, C & E fire.
- Incorporated with high pressure external CO₂ cartridge.
- Easy maintenance.
- Field rechargeable.
- Simple and safe operation.
- Safety valve is provided on the cartridge and the main valve to ensure maximum safety.
- Electrostatic powder painting after shot blasting ensures maximum corrosion resistance.

Applications:

External Cartridge extinguishers are designed for the protection of ordinary and high risk hazards. It can be used for reliable fire protection in many industries and applications including Refining, Petro-Chemical, Oil and Natural Gas Production, Mining, Transportation, Utilities, Metal Processing, Paint Process Areas, Welding Areas, Material Storage Areas and many others.

Options

- Special NPC-M series with metal dry powder for class D fire of Magnesium, Sodium etc.
- Special NPC-F series with Sodium Bicarbonate for class B & C fires
- Special PVC internal coating
- Plastic base

Model	NP6	NP12
Extinguisher Capacity	6Kg	12Kg
Working Pressure	14 Bar	
Test Pressure	30 Bar	
Total Weight	11Kg	18.9Kg
Range of Discharge	6-8m	6-8m
Duration of Discharge	14-16 Sec	18-22 Sec
Operating Temperature	-20°C to +60°C	