

PORTABLE CARBON DIOXIDE EXTINGUISHERS



Design features

- Manufactured as per BS EN3 Standards.
- Exceptionally effective on Class B, C & E fire.
- Easy to handle.
- Completely safe fire extinguishing agent.
- Colourless and odourless agent and hence would not contaminate food and other valuable materials.
- Highly effective for use on electrical equipment with out any risk to operator.
- Unbreakable rising pipe made of Aluminium to ensure long lasting life.
- Cylinder made of special steel to withstand high pressures and it is tested at 250bar.
- High gloss polyester finish after sand blasting prevents chipping.
- Safety valve is fitted in each extinguisher for maximum safety.
- Snow horns with built-in nozzle produces a jet of extinguishing gas for fast fire suppression.
- Special hangers for wall mounting.



Model	NC 2	NC 5-L	NC 3	NC 10-L	NC 5	NC 6
Capacity of extinguisher	2 Kg	5Lbs	3 Kg	10 Lbs	5 Kg	6 Kg
Average height with valve, cm	62	62	50	70	73	85
Hose length with horn, cm	-	-	-	75	75	75
Average Total weight, Kg	8.6	8.6	12.8	16.7	17.5	19.5
Test Pressure, Bar	250	250	250	250	250	250
Duration of discharge, sec	8	10	10	12	13	15
Range of discharge, m	4-5	4-5	4-5	4-5	4-5	4-5
Operating Temperature	-20°C to +60°C					

AREAS OF APPLICATIONS OF CARBON DIOXIDE EXTINGUISHERS

- FLAMMABLE LIQUID STORAGE AREAS
- AIRPORTS
- DATA PROCESSING CENTRES
- CHEMICAL PLANTS & LABORATORIES
- PETROCHEMICAL INDUSTRIES
- ELECTRICAL CONTROL PANELS
- FOOD STORAGE AND PROCESSING PLANTS
- TELEPHONE EQUIPMENT ROOMS
- ENGINE ROOMS
- QUENCH TANKS
- SPRAY BOOTHS
- CONTROL ROOMS



National Fire Fighting Manufacturing Co. Ltd.

Tel: (971 4) 8815653, Fax: (971 4) 8816229

e-mail: natfire@emirates.net.ae

P.O. Box 17014, Dubai, U.A.E.

Website: www.naffco.com

APPROVED ISO 9001 QUALITY MANUFACTURER



WE RESERVE THE RIGHT TO MODIFY SPECIFICATIONS WITHOUT PRIOR NOTICE CAT. NO. NF/CO₂ P/01/01A