



COMBAT®

PORTABLE FIRE EXTINGUISHERS

COMBAT® has an extensive variety of portable extinguishers ranging from ABC Dry Power, Halotron 1, Carbon Dioxide, Foam and Water Fire Extinguishers.

ABC DRY POWER STORE PRESSURE EXTINGUISHER

Blue Colour Band

- Approved To BSEN3
- Comply to AS/NZS 1841:1997
- Top Quality Fire Extinguisher
- Effective Suppression for Class A, B, C & E Fires
- Non-Conductive of Electricity
- Fast Knock Out Effect
- Signal Red (RAL3000) Epoxy Polyester Power Coating
- Widely Used in Commercial Buildings, Industrial Plants, Workshops etc.



Model	C-1ASE	C-2ASE	C-3ASE	C-4ASE	C-6ASE	C-9ASE	C-12ASE	C-20BC	C-9PKSE
Capacity (kg)	1.0	2.0	3.0	4.0	6.0	9.0	12.0	9.0	9.0
Extinguishing Medium	ABC 40% Dry Chemical Power							STD BC Power	Purple K
Fire Rating	5A/21B	8A/34B	13A/55B	13A/70B	21A/113B	27A/144B	27A/144B	70B	144B
Class of Fire	A, B, C & Electrical							B, C & Electrical	
Overall Height (mm)	325	460	477	484	525	612	612	612	612
Diameter (mm)	85	98	116	150	190	190	190	190	190
Empty Weight (kg)	1.09	1.58	1.96	2.53	3.47	4.09	4.09	4.09	4.09
Full Weight (kg)±	2.09	3.58	4.96	6.53	9.47	13.09	16.09	13.09	13.09
Min. Discharge Time (Sec)	6.1	6.9	11.7	15	16	17	30	13.3/15.9	13.3
Min. Discharge Range (M)	3	3	3	5	5	7	7	7	7
Approved by LPCB (UK)	✓	✓	✓	✓	✓	✓	-	-	-
Approved by PSB	✓	✓	✓	✓	✓	✓	-	-	✓

The company reserves the right to change the specification without prior notice.

GENERAL INFORMATION

Operating Temperature Range	Safe Operating Distance	Propellant Type	Max Working Pressure	Test Pressure
20°C to +60°C	2 meter	Nitrogen	14kgf/cm ²	22.5 bar

COMBAT®