



TECHNICAL DATA

SOLID CONE SPRAY NOZZLES

The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058

Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com

1. DESCRIPTION

Viking Model A-2, A-2X, B-2, C-2, and D-2 Solid Cone Spray Nozzles are "non-automatic" pattern, open, directional discharge spray nozzles. The spray nozzle units feature two-piece construction consisting of a cast bronze body and threaded insert. The insert determines the included angle of discharge and the body construction provides a uniform distribution throughout the discharge pattern. When spraying, the nozzle discharge forms a solid, cone-shaped spray pattern meeting the requirements for medium- and high-velocity water spray systems.

Optional dust plugs are available to prevent foreign material from entering the open end of the spray nozzle. They are designed to blow off when the system piping is pressurized.

2. LISTINGS AND APPROVALS

cULus Listed: Category VGYZ

FM Approved: Water-Spray Systems-consult FM Approval Guide for acceptable applications.

NYC Approved: Calendar Number 219-76-SA, Bulletin No. 16, Vol. LXI

NOTE: International approval certificates are available upon request.

The nozzles are approved for use in medium- and high-velocity water spray systems. Refer to the Approval Charts on pages 23-24 and Design Criteria on page 25 for cULus and FM approval requirements that must be followed.

3. TECHNICAL DATA

Specifications:

Available since 1971.

The water inlet is at a 90° angle to the nozzle outlet. The smallest nozzle passage is 1/4" (6 mm) for Part Nos. 05133AAJ through 05134AJN; 11/32" (9 mm) for Part Nos. 05135AAJ through 05135AJN; 3/8" (10 mm) for Part Nos. 05136AAJ through 05136AJN; and 7/16" (11 mm) for Part Nos. 05137AAJ through 05137AJN.

All bodies are permanently marked with the model number.

All inserts are permanently marked with the angle of discharge and model.

Inserts may be stamped with more than one model, which indicates the insert may be interchanged with either type of nozzle body.

Inserts are available in spray angles of 30°, 60°, 90°, 120°, and 140°, and are interchangeable in a given body model.

Refer to pages 25-29 for spray nozzle water distribution patterns.

Thread size: 1/2" (15 mm) NPT male thread is standard

Nominal K-Factors: Refer to the Approval Charts

Dust Plugs (Optional):

Red Polyethylene Cap: 1" (25 mm) deep

Rated for a continuous temperature of 220 °F (104 °C).

Spray Nozzle Material Standards:


Body Casting: Brass UNS-C84400

Insert: Brass UNS-C36000

Ordering Information: (Also refer to the current [Viking price list](#).)


Order Model A-2, A-2X, B-2, C-2, and D-2 Solid Cone Spray Nozzles by selecting the appropriate part number from the Approval Charts.

Available Finishes: Brass or Electroless Nickel. Refer to the Approval Charts



Solid Cone Spray Nozzles

Viking Technical Data may be found on
The Viking Corporation's Web site at
<http://www.vikinggroupinc.com>.
The Web site may include a more recent
edition of this Technical Data Page.



Spray Nozzle Dust Plug



TECHNICAL DATA

SOLID CONE
SPRAY NOZZLES

The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058

Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com

For example, Spray Nozzle Model A-2 (VK740) with a 1.2 K-Factor, a 30° spray angle, and a Brass finish = Part No. 05133AAJ

Dust Plugs (Optional): Dust plugs are used to prevent the depositing of foreign materials in the waterway, which could interfere with the discharge of the spray nozzles. The plugs are designed to blow off when the system piping is pressurized.

Part Number 02409A for use with Spray Nozzle Part Nos. 05133AAJ through 05135AJN.

Part Number 02410A for use with Spray Nozzle Part Nos. 05136AAJ through 05137AJN.

4. INSTALLATION

WARNING: Viking Model A-2, A-2X, B-2, C-2, and D-2 Solid Cone Spray Nozzles are manufactured and tested to meet the rigid requirements of the approving agency. The nozzles are designed to be installed in accordance with recognized installation standards. Deviation from the standards or any alteration to the nozzle after it leaves the factory including, but not limited to: painting, plating, coating, or modification, may render the unit inoperative and will automatically nullify the approval and any guarantee made by The Viking Corporation.

The Approval Charts on pages 23-24 show listings and approvals of Model A-2, A-2X, B-2, C-2, and D-2 Spray Nozzles for use on water spray systems. The charts show listings and approvals available at the time of printing. Other approvals are in process. Check with the manufacturer for any additional approvals.

- A. **Spray nozzles are to be installed in accordance with the latest edition of Viking technical data, the latest published standards of NFPA, FM Global, LPCB, APSAD, VdS or other similar organizations, and also with the provisions of governmental codes, ordinances, and standards whenever applicable. The use of Model A-2, A-2X, B-2, C-2, and D-2 Spray Nozzles may be limited due to occupancy and hazard. Refer to the Authority Having Jurisdiction prior to installation.**
- B. Spray nozzles are installed on fixed fire protection systems, such as deluge systems, where total flooding is required.
- C. Handle Spray Nozzles with care. They must be stored in a cool, dry place in their original shipping container. Never install a spray nozzle that has been dropped or damaged.
- D. Corrosion-resistant spray nozzles must be installed when subject to corrosive atmospheres. When installing corrosion resistant nozzles, take care not to damage the corrosion resistant coating.
- E. Spray nozzles must be installed after the piping is in place to prevent mechanical damage.
- F. Before installing, be sure to have the appropriate model, with the correct K-Factor, spray angle, and insert. Spray nozzle bodies are permanently marked with the model number. All inserts are permanently marked with the angle of discharge and model. Inserts may be stamped with more than one model, which indicates the insert may be interchanged with either type of nozzle body.
 1. Apply a small amount of pipe-joint compound or tape to the external threads of the spray nozzle only, taking care not to allow a build-up of compound inside the inlet.
 2. Install the nozzle on the fixed piping using a standard crescent wrench. Take care not to over-tighten or damage the spray nozzle.
- G. Spray nozzles must be protected from mechanical damage. Where open spray nozzles are used, care must be taken to prevent foreign materials from entering the orifice. Foreign materials may accumulate and restrict or plug the waterway and may prevent proper operation of the spray nozzle.
- H. Install dust plugs (if used): After installing the spray nozzle unit, press the dust cover over the end of the nozzle insert.

5. OPERATION

Model A-2, A-2X, B-2, C-2, and D-2 Solid Cone Spray Nozzles are designed to apply cooling water to exposed vertical, horizontal, curved, and irregular shaped surfaces to allow cooling of objects externally when exposed to an adjacent fire. Cooling is done to prevent objects from absorbing heat that could cause structural damage and possible spread of fire to the protected object. In some applications, Model A-2, A-2X, B-2, C-2, and D-2 Spray Nozzles may be applied to control or extinguish fire of the protected area (depending on water design application density).

6. INSPECTIONS, TESTS AND MAINTENANCE

NOTICE: The owner is responsible for maintaining the fire protection system and devices in proper operating condition. For minimum maintenance and inspection requirements, refer to the NFPA standard (e.g., NFPA 25) that describes care and maintenance of sprinkler systems. In addition, the Authority Having Jurisdiction may have additional maintenance, testing, and inspection requirements that must be followed.

<h1>VIKING</h1>	<h2>TECHNICAL DATA</h2>	<h3>SOLID CONE SPRAY NOZZLES</h3>
-----------------	-------------------------	---------------------------------------

The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058
 Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com

TABLE 1: SPRAY NOZZLE DIMENSIONS

SIN	A	B	C	D	E	F	G	H
VK740-VK769	1-7/8" (48 mm)	7/8" (22 mm)	1/2" (13 mm)	1-5/8" (41 mm)	13/16" (21 mm)	5/16" (8 mm)	1-17/64" (32 mm)	1-11/16" (43 mm)
VK770-VK789	2-1/16" (52 mm)	1" (25 mm)	5/8" (16 mm)	2-3/16" (56 mm)	1" (25 mm)	3/8" (10 mm)	1-17/32" (39 mm)	2" (51 mm)




Figure 1: Spray Nozzle Dimensions



The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058
 Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com

Approval Chart 1																	
Model A-2, A-2X, B-2, C-2, and D-2 Spray Nozzles - Brass Finish																	
Part Number ¹	SIN	Nominal K-Factor		Angle	Listings and Approvals ³ (Refer also to Design Criteria on page 25.)				Part Number ¹	SIN	Nominal K-Factor		Angle	Listings and Approvals ³ (Refer also to Design Criteria on page 25.)			
		U.S.	metric ²		cULus ⁴	NYC ⁵	FM	LPCB			U.S.	metric ²		cULus ⁴	NYC ⁵	FM	LPCB
Model A-2 Brass Finish																	
05133AAJ	VK740	1.2	17.3	30°	Yes	Yes	Yes	Yes	05133AAM	VK743	1.4	20.2	120°	Yes	Yes	Yes	Yes
05133AAK	VK741	1.2	17.3	60°	Yes	Yes	Yes	Yes	05133AAN	VK744	1.4	20.2	140°	Yes	Yes	Yes	Yes
05133AAL	VK742	1.2	17.3	90°	Yes	Yes	Yes	Yes	--	--	--	--	--	--	--	--	--
Model A-2X Brass Finish																	
05134AAJ	VK750	2.0	28.8	30°	Yes	Yes	Yes	--	05134AAM	VK753	2.2	31.7	120°	Yes	Yes	Yes	--
05134AAK	VK751	2.0	28.8	60°	Yes	Yes	Yes	--	05134AAN	VK754	2.2	31.7	140°	Yes	Yes	Yes	--
05134AAL	VK752	2.0	28.8	90°	Yes	Yes	Yes	--	--	--	--	--	--	--	--	--	--
Model B-2 Brass Finish																	
05135AAJ	VK760	2.8	40.4	30°	Yes	Yes	Yes	Yes	05135AAM	VK763	3.3	47.6	120°	Yes	Yes	Yes	Yes
05135AAK	VK761	2.8	40.4	60°	Yes	Yes	Yes	Yes	05135AAN	VK764	3.3	47.6	140°	Yes	Yes	Yes	Yes
05135AAL	VK762	2.8	40.4	90°	Yes	Yes	Yes	Yes	--	--	--	--	--	--	--	--	--
Model C-2 Brass Finish																	
05136AAJ	VK770	3.4	49.0	30°	Yes	Yes	Yes	Yes	05136AAM	VK773	3.9	56.2	120°	Yes	Yes	Yes	Yes
05136AAK	VK771	3.4	49.0	60°	Yes	Yes	Yes	Yes	05136AAN	VK774	3.9	56.2	140°	Yes	Yes	Yes	Yes
05136AAL	VK772	3.8	54.8	90°	Yes	Yes	Yes	Yes	--	--	--	--	--	--	--	--	--
Model D-2 Brass Finish																	
05137AAJ	VK780	4.7	67.8	30°	Yes	Yes	Yes	Yes	05137AAM	VK783	5.2	75.0	120°	Yes	Yes	Yes	Yes
05137AAK	VK781	4.7	67.8	60°	Yes	Yes	Yes	Yes	05137AAN	VK784	5.2	75.0	140°	Yes	Yes	Yes	Yes
05137AAL	VK782	5.0	72.1	90°	Yes	Yes	Yes	Yes	--	--	--	--	--	--	--	--	--
Footnotes																	
¹ Spray nozzle bodies are permanently marked with the model number. All inserts are permanently marked with the angle of discharge and model. Inserts may be stamped with more than one model, which indicates the insert may be interchanged with either type of nozzle body. ² Metric K-Factor shown is when pressure is measured in Bar. When pressure is measured in kPa, divide the metric K-Factor shown by 10.0. ³ This table shows the listings and approvals available at the time of printing. Check with the manufacturer for any additional approvals. ⁴ Listed by Underwriters Laboratories Inc. for use in the U.S. and Canada. ⁵ Approved by the NYC Board of Standards and Appeals, MEA No. 219-76-SA, Bulletin No. 16, Vol. LXI.																	



TECHNICAL DATA

SOLID CONE SPRAY NOZZLES

The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058

Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com

Approval Chart 2

Model A-2, A-2X, B-2, C-2, and D-2 Spray Nozzles - Electroless Nickel Finish

Part Number ¹	SIN	Nominal K-Factor		Angle	Listings and Approvals ³ (Refer also to Design Criteria on page 25.)				Part Number ¹	SIN	Nominal K-Factor		Angle	Listings and Approvals ³ (Refer also to Design Criteria on page 25.)			
		U.S.	metric ²		cULus ⁴	NYC ⁵	FM	LPCB			U.S.	metric ²		cULus ⁴	NYC ⁵	FM	LPCB
Model A-2 Electroless Nickel Finish																	
05133AJJ	VK740	1.2	17.3	30°	Yes	Yes	Yes	Yes	05133AJM	VK743	1.4	20.2	120°	Yes	Yes	Yes	Yes
05133AJK	VK741	1.2	17.3	60°	Yes	Yes	Yes	Yes	05133AJN	VK744	1.4	20.2	140°	Yes	Yes	Yes	Yes
05133AJL	VK742	1.2	17.3	90°	Yes	Yes	Yes	Yes	--	--	--	--	--	--	--	--	--
Model A-2X Electroless Nickel Finish																	
05134AJJ	VK750	2.0	28.8	30°	Yes	Yes	Yes	Yes	05134AJM	VK753	2.2	31.7	120°	Yes	Yes	Yes	Yes
05134AJK	VK751	2.0	28.8	60°	Yes	Yes	Yes	Yes	05134AJN	VK754	2.2	31.7	140°	Yes	Yes	Yes	Yes
05134AJL	VK752	2.0	28.8	90°	Yes	Yes	Yes	Yes	--	--	--	--	--	--	--	--	--
Model B-2 Electroless Nickel Finish																	
05135AJJ	VK760	2.8	40.4	30°	Yes	Yes	Yes	Yes	05135AJM	VK763	3.3	47.6	120°	Yes	Yes	Yes	Yes
05135AJK	VK761	2.8	40.4	60°	Yes	Yes	Yes	Yes	05135AJN	VK764	3.3	47.6	140°	Yes	Yes	Yes	Yes
05135AJL	VK762	2.8	40.4	90°	Yes	Yes	Yes	Yes	--	--	--	--	--	--	--	--	--
Model C-2 Electroless Nickel Finish																	
05136AJJ	VK770	3.4	49.0	30°	Yes	Yes	Yes	Yes	05136AJM	VK773	3.9	56.2	120°	Yes	Yes	Yes	Yes
05136AJK	VK771	3.4	49.0	60°	Yes	Yes	Yes	Yes	05136AJN	VK774	3.9	56.2	140°	Yes	Yes	Yes	Yes
05136AJL	VK772	3.8	54.8	90°	Yes	Yes	Yes	Yes	--	--	--	--	--	--	--	--	--
Model D-2 Electroless Nickel Finish																	
05137AJJ	VK780	4.7	67.8	30°	Yes	Yes	Yes	Yes	05137AJM	VK783	5.2	75.0	120°	Yes	Yes	Yes	Yes
05137AJK	VK781	4.7	67.8	60°	Yes	Yes	Yes	Yes	05137AJN	VK784	5.2	75.0	140°	Yes	Yes	Yes	Yes
05137AJL	VK782	5.0	72.1	90°	Yes	Yes	Yes	Yes	--	--	--	--	--	--	--	--	--

Footnotes

¹ Spray nozzle bodies are permanently marked with the model number. All inserts are permanently marked with the angle of discharge and model. Inserts may be stamped with more than one model, which indicates the insert may be interchanged with either type of nozzle body.

² Metric K-Factor shown is when pressure is measured in Bar. When pressure is measured in kPa, divide the metric K-Factor shown by 10.0.

³ This table shows the listings and approvals available at the time of printing. Check with the manufacturer for any additional approvals.

⁴ Listed by Underwriters Laboratories Inc. for use in the U.S. and Canada.

⁵ Approved by the NYC Board of Standards and Appeals, MEA No. 219-76-SA, Bulletin No. 16, Vol. LXI.



TECHNICAL DATA

SOLID CONE SPRAY NOZZLES

The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058

Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com

DESIGN CRITERIA

(Also refer to the Approval Charts on pages 23-24.)

cULus Listing Requirements:

Refer to the installation standards, such as NFPA 15, for minimum water supply requirements, nozzle pressure, and installation guidelines.

FM Approval Requirements:

Consult FM Approval Guide for acceptable applications. For installation in accordance with the latest applicable FM Loss Prevention Data Sheets and Technical Advisory Bulletins. FM Global Loss Prevention Data Sheets and Technical Advisory Bulletins contain guidelines relating to, but not limited to: minimum water supply requirements, hydraulic design, ceiling slope and obstructions, minimum and maximum allowable spacing, and distance below the ceiling.

NOTE: The FM installation guidelines may differ from cULus and/or NFPA criteria.

IMPORTANT: Always refer to Bulletin Form No. F_091699 - Care and Handling of Sprinklers. Viking spray nozzles are to be installed in accordance with the latest edition of Viking technical data, the appropriate standards of NFPA, FM Global, LPCB, APSAD, VdS or other similar organizations, and also with the provisions of governmental codes, ordinances, and standards, whenever applicable.

- A. Spray nozzles must be inspected on a regular basis for corrosion, mechanical damage, obstructions, paint, etc. Where open spray nozzles are installed, verify that foreign materials (such as dust, dirt, etc.) do not restrict or plug the waterspray. The frequency of inspections may vary due to corrosive atmospheres, water supplies, and activity around the device. It is also recommended that outdoor installations of Solid Cone Spray Nozzles with dust plugs be periodically inspected, during freezing weather conditions, for the presence of ice buildup from trapped condensate which could effect the proper release of the plugs.
- B. Spray nozzles that have been painted or mechanically damaged must be replaced immediately. Nozzles showing signs of corrosion shall be tested and/or replaced immediately as required. When replacing spray nozzles, use only new spray nozzles.
 1. Using a standard crescent wrench, remove the old spray nozzle and install the new unit. Care must be taken to ensure that the replacement spray nozzle is the proper model, with the correct K-Factor and insert. Spray nozzle bodies are permanently marked with the model number. All inserts are permanently marked with the angle of discharge and model. Inserts may be stamped with more than one model, which indicates the insert may be interchanged with either type of nozzle body.
- C. The spray nozzle discharge pattern is critical for proper fire protection. Therefore, nothing should be hung from, attached to, or otherwise obstruct the discharge pattern. All obstructions must be immediately removed or, if necessary, additional nozzles installed.
- D. Fire protection systems that have been subjected to a fire must be returned to service as soon as possible. The entire system must be inspected for damage and repaired or replaced as necessary. Spray nozzles that have been exposed to corrosive products of combustion or high ambient temperatures, should be replaced. Refer to the Authority Having Jurisdiction for minimum replacement requirements.

7. AVAILABILITY

The Viking Model A-2, A-2X, B-2, C-2, and D-2 Solid Cone Spray Nozzles are available through a network of domestic and international distributors. See The Viking Corporation web site for the closest distributor or contact The Viking Corporation.

8. GUARANTEE

For details of warranty, refer to Viking's current list price schedule or contact Viking directly.




TECHNICAL DATA

SOLID CONE SPRAY NOZZLES - WATER DISTRIBUTION PATTERNS

The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058


Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com




Spray Nozzle Model:
A2X (VK750-VK754†)
Spray Nozzle Base P/Ns:
05134AA & 05134AJ*
Angle: 30°
Thread Size: 1/2" NPT
K-Factor: 2.0 U.S. (28.8 metric)

LEGEND
10 P.S.I. - - - - -
20 P.S.I. ······
30 P.S.I. - - - - -
50 P.S.I. _____


Top View-Horizontal Spray



Side View-Horizontal Spray




Side View Spray Up




Spray Nozzle Model:
A2X (VK750-VK754†)
Spray Nozzle Base P/Ns:
05134AA & 05134AJ*
Angle: 60°
Thread Size: 1/2" NPT
K-Factor: 2.0 U.S. (28.8 metric)

LEGEND
10 P.S.I. - - - - -
20 P.S.I. ······
30 P.S.I. - - - - -
50 P.S.I. _____


Top View-Horizontal Spray



Side View-Horizontal Spray




Side View Spray Up




Spray Nozzle Model:
A2X (VK750-VK754†)
Spray Nozzle Base P/Ns:
05134AA & 05134AJ*
Angle: 90°
Thread Size: 1/2" NPT
K-Factor: 2.0 U.S. (28.8 metric)

LEGEND
10 P.S.I. - - - - -
20 P.S.I. ······
30 P.S.I. - - - - -
50 P.S.I. _____


Top View-Horizontal Spray



Side View-Horizontal Spray




Side View Spray Up




Spray Nozzle Model:
A2X (VK750-VK754†)
Spray Nozzle Base P/Ns:
05134AA & 05134AJ*
Angle: 120°
Thread Size: 1/2" NPT
K-Factor: 2.2 U.S. (31.7 metric)

LEGEND
10 P.S.I. - - - - -
20 P.S.I. ······
30 P.S.I. - - - - -
50 P.S.I. _____

Top View-Horizontal Spray



Side View-Horizontal Spray



Side View Spray Up

Scale: Each square equals one square foot. †Spray Nozzle Identification Numbers provided in accordance with the 1999 edition of NFPA 13, Section 3-2.2. * Base part numbers shown. For complete part number, refer to Viking's current price list.




TECHNICAL DATA

SOLID CONE SPRAY NOZZLES - WATER DISTRIBUTION PATTERNS

The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058

Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com




Spray Nozzle Model:
A2X (VK750-VK754†)
Spray Nozzle Base P/Ns:
05134AA & 05134AJ*
Angle: 140°
Thread Size: 1/2" NPT
K-Factor: 2.2 U.S. (31.7 metric)


LEGEND

- 10 P.S.I. - - - - -
- 20 P.S.I. ·····
- 30 P.S.I. - - - - -
- 50 P.S.I. ———


Top View-Horizontal Spray



Side View-Horizontal Spray



Side View Spray Up




Spray Nozzle Model:
A2 (VK740-VK744†)
Spray Nozzle Base P/Ns:
05133AA & 05133AJ*
Angle: 30°
Thread Size: 1/2" NPT
K-Factor: 1.2 U.S. (17.3 metric)


LEGEND

- 10 P.S.I. - - - - -
- 20 P.S.I. ·····
- 30 P.S.I. - - - - -
- 50 P.S.I. ———


Top View-Horizontal Spray



Side View-Horizontal Spray



Side View Spray Up




Spray Nozzle Model:
A2 (VK740-VK744†)
Spray Nozzle Base P/Ns:
05133AA & 05133AJ*
Angle: 60°
Thread Size: 1/2" NPT
K-Factor: 1.2 U.S. (17.3 metric)


LEGEND

- 10 P.S.I. - - - - -
- 20 P.S.I. ·····
- 30 P.S.I. - - - - -
- 50 P.S.I. ———


Top View-Horizontal Spray



Side View-Horizontal Spray



Side View Spray Up




Spray Nozzle Model:
A2 (VK740-VK744†)
Spray Nozzle Base P/Ns:
05133AA & 05133AJ*
Angle: 90°
Thread Size: 1/2" NPT
K-Factor: 1.2 U.S. (17.3 metric)


LEGEND

- 10 P.S.I. - - - - -
- 20 P.S.I. ·····
- 30 P.S.I. - - - - -
- 50 P.S.I. ———

Top View-Horizontal Spray



Side View-Horizontal Spray



Side View Spray Up

Scale: Each square equals one square foot. †Spray Nozzle Identification Numbers provided in accordance with the 1999 edition of NFPA 13, Section 3-2.2.
* Base part numbers shown. For complete part number, refer to Viking's current price list.



TECHNICAL DATA

SOLID CONE SPRAY NOZZLES - WATER DISTRIBUTION PATTERNS


The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058

Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com


Spray Nozzle Model:
A2 (VK740-VK744†)
Spray Nozzle Base P/Ns:
05133AA & 05133AJ*
Angle: 120°
Thread Size: 1/2" NPT
K-Factor: 1.4 U.S. (20.2 metric)

LEGEND


10 P.S.I. - - - - -
20 P.S.I. ······
30 P.S.I. - - - - -
50 P.S.I. _____



Top View-Horizontal Spray



Side View-Horizontal Spray




Side View Spray Up


Spray Nozzle Model:
A2 (VK740-VK744†)
Spray Nozzle Base P/Ns:
05133AA & 05133AJ*
Angle: 140°
Thread Size: 1/2" NPT
K-Factor: 1.4 U.S. (20.2 metric)

LEGEND


10 P.S.I. - - - - -
20 P.S.I. ······
30 P.S.I. - - - - -
50 P.S.I. _____



Top View-Horizontal Spray



Side View-Horizontal Spray




Side View Spray Up


Spray Nozzle Model:
B2 (VK760-VK764†)
Spray Nozzle Base P/Ns:
05135AA & 05135AJ*
Angle: 30°
Thread Size: 1/2" NPT
K-Factor: 2.8 U.S. (40.4 metric)

LEGEND


10 P.S.I. - - - - -
20 P.S.I. ······
30 P.S.I. - - - - -
50 P.S.I. _____



Top View-Horizontal Spray



Side View-Horizontal Spray




Side View Spray Up


Spray Nozzle Model:
B2 (VK760-VK764†)
Spray Nozzle Base P/Ns:
05135AA & 05135AJ*
Angle: 60°
Thread Size: 1/2" NPT
K-Factor: 2.8 U.S. (40.4 metric)

LEGEND


10 P.S.I. - - - - -
20 P.S.I. ······
30 P.S.I. - - - - -
50 P.S.I. _____



Top View-Horizontal Spray



Side View-Horizontal Spray



Side View Spray Up

Scale: Each square equals one square foot. †Spray Nozzle Identification Numbers provided in accordance with the 1999 edition of NFPA 13, Section 3-2.2. * Base part numbers shown. For complete part number, refer to Viking's current price list.




TECHNICAL DATA


SOLID CONE SPRAY
NOZZLES - WATER
DISTRIBUTION PATTERNS

The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058

Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com




Top View-Horizontal Spray




Side View-Horizontal Spray

Side View Spray Up




Top View-Horizontal Spray




Side View-Horizontal Spray

Side View Spray Up




Top View-Horizontal Spray




Side View-Horizontal Spray

Side View Spray Up




Top View-Horizontal Spray



Side View-Horizontal Spray

Side View Spray Up

Scale: Each square equals one square foot. †Spray Nozzle Identification Numbers provided in accordance with the 1999 edition of NFPA 13, Section 3-2.2.
* Base part numbers shown. For complete part number, refer to Viking's current price list.




TECHNICAL DATA

SOLID CONE SPRAY NOZZLES - WATER DISTRIBUTION PATTERNS

The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058

Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com




Spray Nozzle Model:
C2 (VK770-VK774†)
Spray Nozzle Base P/Ns:
05136AA & 05136AJ*
Angle: 60°
Thread Size: 1/2" NPT
K-Factor: 3.4 U.S. (49.0 metric)


LEGEND

- 10 P.S.I. - - - - -
- 20 P.S.I. ······
- 30 P.S.I. - · - · -
- 50 P.S.I. _____


Top View-Horizontal Spray



Side View-Horizontal Spray



Side View Spray Up




Spray Nozzle Model:
C2 (VK770-VK774†)
Spray Nozzle Base P/Ns:
05136AA & 05136AJ*
Angle: 90°
Thread Size: 1/2" NPT
K-Factor: 3.8 U.S. (54.8 metric)


LEGEND

- 10 P.S.I. - - - - -
- 20 P.S.I. ······
- 30 P.S.I. - · - · -
- 50 P.S.I. _____


Top View-Horizontal Spray



Side View-Horizontal Spray



Side View Spray Up




Spray Nozzle Model:
C2 (VK770-VK774†)
Spray Nozzle Base P/Ns:
05136AA & 05136AJ*
Angle: 120°
Thread Size: 1/2" NPT
K-Factor: 3.9 U.S. (56.2 metric)


LEGEND

- 10 P.S.I. - - - - -
- 20 P.S.I. ······
- 30 P.S.I. - · - · -
- 50 P.S.I. _____


Top View-Horizontal Spray



Side View-Horizontal Spray



Side View Spray Up




Spray Nozzle Model:
C2 (VK770-VK774†)
Spray Nozzle Base P/Ns:
05136AA & 05136AJ*
Angle: 140°
Thread Size: 1/2" NPT
K-Factor: 3.9 U.S. (56.2 metric)


LEGEND

- 10 P.S.I. - - - - -
- 20 P.S.I. ······
- 30 P.S.I. - · - · -
- 50 P.S.I. _____

Top View-Horizontal Spray



Side View-Horizontal Spray



Side View Spray Up

Scale: Each square equals one square foot. †Spray Nozzle Identification Numbers provided in accordance with the 1999 edition of NFPA 13, Section 3-2.2.
* Base part numbers shown. For complete part number, refer to Viking's current price list.




TECHNICAL DATA


SOLID CONE SPRAY NOZZLES - WATER DISTRIBUTION PATTERNS

The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058


Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com




Top View-Horizontal Spray




Top View-Horizontal Spray




Side View-Horizontal Spray




Side View Spray Up




Side View-Horizontal Spray




Side View Spray Up




Top View-Horizontal Spray




Top View-Horizontal Spray




Side View-Horizontal Spray



Side View Spray Up



Side View-Horizontal Spray



Side View Spray Up

Scale: Each square equals one square foot. †Spray Nozzle Identification Numbers provided in accordance with the 1999 edition of NFPA 13, Section 3-2.2.
* Base part numbers shown. For complete part number, refer to Viking's current price list.




TECHNICAL DATA

SOLID CONE SPRAY
NOZZLES - WATER
DISTRIBUTION PATTERNS

The Viking Corporation, 210 N Industrial Park Road, Hastings MI 49058

Telephone: 269-945-9501 Technical Services 877-384-5464 Fax: 269-945-4495 Email: techsvcs@vikingcorp.com




Top View-Horizontal Spray


Spray Nozzle Model:
D2 (VK780-VK784†)
Spray Nozzle Base P/Ns:
05137AA & 05137AJ*
Angle: 140°
Thread Size: 1/2" NPT
K-Factor: 5.2 U.S. (75.0
metric)

LEGEND

- 10 P.S.I. - - - - -
- 20 P.S.I. ······
- 30 P.S.I. - · - · -
- 50 P.S.I. _____



Side View-Horizontal Spray



Side View Spray Up

Scale: Each square equals one square foot. †Spray Nozzle Identification Numbers provided in accordance with the 1999 edition of NFPA 13, Section 3-2.2.
* Base part numbers shown. For complete part number, refer to Viking's current price list.

**THIS PAGE
INTENTIONALLY
LEFT BLANK**