

KIV - 201C



**KIV - 201C**  
**4" Color LCD Monitor**

- Hands-Free System
- Communication
- 4 Wired in polarity
- Door Release
- Wide view angle
- Easy Installation

**KIV - 201C Function**

- For Multiple Families, Villa, Mension & Apartment
- 4" Color LCD Monitor
- Hands-free System
- Communication
  - Monitor to Door Camera
  - Monitor to Guard Office Interphone (Audio only)
- 4 Wired in polarity
- Door Release Function
- Wide view angle
  - Wide view angle(120°)not necessary to adjust camera view angle
  - Clean picture through circuit of image compensation in bright back light
- Easy Installation
- Power AC 110V or 220V
- DC Type Available

**KIV - 201C Specification**

ITEM	Specification
Power	SMPS TYPE(AC 220V or 110V, 50 or 60Hz)
Power consumption	Max 19W, Stand by 2W
Assurance temperature	0 ~ 50°C
Communication system	One Way Handsfree
TFT LCD	4" Color TFT LCD
Wiring	4 Wired in polarity
Max Wiring Distance	∅0.65 Single Cable/50m, 5C-2V Coaxial Cable / 100m
Dimension	310(W) X 240(H) X 15(D)mm

KC - C60



**KC - C60  
Door Camera**

- Wide view Angle
- Communication

**KC - C60 Function**

- For Multiple Families, Villa, Mension & Apartment
- Wide view angle
  - Wide view angle(120°)not necessary to adjust camera view angle
  - Clean picture through circuit of image compensation in bright back light
- Communication

**KC - C60 Specification**

ITEM	Specification
Power	DC 12V ±1V (Power from monitor)
Power consumption	Max 2.5W
Assurance temperature	-10°C ~ 50°C
Image Sensor	1/3"CCD (270,000/320,000 Pixels)
Scanning Frequency	Horizontal 15,625KHz or 15,732KHz / Vertical 50Hz or 60Hz
Lens	F:20., f=3.0mm
Output Impedance	Picture : 75 omh Voice : 600 ohm
Minimum illumination	0.1Lux(LED ON)
Angle of Picture	Diagonal:120°, angle adjustable
TV System	PAL or NTSC
Installation	Embedment Type
Dimension	95(W) X 127(H) X 46(D)mm

■ The product may include option or additional functions.