

KVM-604



KVM - 604 Function

- Easy Installation & High Quality, 4 Wired Series
- SMPS Type(Dual 110V ~ 220V)
- 4" CRT Monitor
- Easy Installation
- Max. 3Monitors Parallel Connectable with 1 Camera
- 4 Wired in polarity
- Wide View Angle 120°
 - Not necessary to adjust camera view angle
- Door Release Function
 - Can be combined with door opener(DO-12/option)

KVM - 604 Specification

	ITEM	Specification
	Power	Built-in AC 110V~220V Free Voltage
	Power consumption	Max 15W, Stand by 2W
	Assurance temperature	0 ~ 50°C
	Braun tube	4 inch Flat Tube(B/W)
Monitor	Communication	Duplex handset conversation
	Wiring	4 Wired in polarity (VCC/GND/VOICE/PICTURE)
	Max Wiring Distancer	∅0.65 Single Cable/50m, 5C-2V Coaxial Cable / 100m
	Dimension	204(W) X 210(H) X 53(D)mm
	Power	DC12±1V (power from monitor)
	Power consumption	Max 2.5W

KOCOM

	Assurance temperature	- 10°C ~ 50°C
	Camera(Image Device)	1/3"CCD (270,000/320,000 Pixels)
	Scanning Frequency	Horizontal 15,625KHz or 15,732KHz / Vertical 50Hz or 60Hz
Camera (KC- D20)	Lens	F:20., f=3.0mm
	Minimum illumination	0.1Lux on the object(IR LED ON)
	Illumination	Infra-red LED
	Angle of picture	Diagonal 90°
	Dimension	95(W) X 127(H) X 32(D)mm

- The product may include option or additional functions.