



Safety for your life



Fire Pump Accessories

Accessories

1

Gate Valve



- Brand : CANATECH - Malaysia
- Model : CA-GATE VALVE
- Size Range : DN50 - DN300
- Working Pressure: 200 PSI
- Design Standard : AWWA C515
- Flange Standard : ANSI B16.1 Clas 125

2

Check Valve



- Brand : CANATECH - Malaysia
- Model : CA-CHECK VALVE
- Size Range : DN50 - DN300
- End Connection : JIS 10K
- Temperature : -10°C ~ 80°C
- Pressure Rating : 10, 16, 20 kgf/cm²

3

Pressure Reduce Valve

Pressure Reduce Valve



- Brand : SHINYI
- Model : D500
- Size Range : DN50 - DN300
- End Connection : JIS 10K
- Temperature : -10°C ~ 80°C
- Pressure Rating : 10, 16, 20 kgf/cm²
- Suitable for water supply, fire - fighting & Irrigation, Drainage & water circulation.

4

Y - Strainer



- Brand : CANATECH - Malaysia
- Model : CA-Y-STRAINER
- Size Range : DN50 - DN300
- Pressure : JIS 10K
- Body : Cast Iron
- Seat : SS304
- End Connection : Flange

Accessories

1

Vortex Inhibitor



- Brand : CANATECH - Malaysia
- Model : CA-VORTEX
- Size Range : DN65 - DN300
- Material : Mild Steel Galvanized
- Flange Type : ANSI

2

Rubber Joint - Stainless Steel



- Brand : CANATECH - Malaysia
- Model : CA-FJS
- Size Range : DN50 - DN300
- Body Material : EPDM Rubber
- Flange : SS304
- Working Pressure : 16 bar
- Operating Temperature : -20 °C ~ 120 °C

3

Rubber Joint - EPDM



- Brand : CANATECH - Malaysia
- Model : CA-FJC
- Size Range : DN50 - DN300
- Body Material : EPDM
- Flange : SS304
- Working Pressure : 16bar

4

Foot Valve



- Brand : CANATECH - Malaysia
- Model : CA-FVS
- Size Range : DN50 - DN300
- Material : SS304
- Connection Method : JIS 10K
- Working Pressure : Max. 1Mpa
- Hydraulic Test : 1,5Mpa

Accessories

1

Pressure Gauge



Flow Meter

- Brand : Badotherm - Holland
- Model : BDT18H
- Design Standard : EN837-1
- Case : AISI304
- Process Connection : ANSI 316 (L)
- Size Gauge : 50, 63, 80, 100, 160mm
- Connection : 1/2" BSP/NPT, 1/4" BSP/NPT
- Min. Range : -1 bar
- Max. Range : 1,600 bar
- Accuracy : 1 - 1.6% FSV

2

Flow Meter



- Brand : Gerand
- Model : K-Meter
- Pipe Size : DN50 - DN250
- Pump GPM : 50 - 300GPM
- Venturi Style : Butt weld, Grooved, Flanged
- Rating : 500Psi
- Material : Stainless Steel
- 4½" Standard Meter Dial
- Accurate to within ±2.0%
- Approved FM

3

Battery & Charger



- Brand : Motolite - Philippines
- Model : G31A-8
- Capacity : 100Ah
- Voltage : 12V
- Dimension : L304 x W173 x H224



- Brand : Vi4t Linh
- Model : AST - 12/24
- Capacity : 20A
- Voltage : 12V or 24V

Accessories

1

Flange - JIS 10K



- Brand : Canatech - Viet Nam
- Size Range : DN15 - DN600
- Standard : JIS 10K
- Number of holes : 4 - 24 holes
- Thickness : 12 - 32(mm)

2

Flange - ANSI



- Brand : Canatech - Viet Nam
- Size Range : DN15 - DN600
- Standard : ANSI B16.5 Class 150/300
- Number of holes : 4 - 20 holes
- Thickness : 12 - 48(mm)

3

Flange - BS4504



- Brand : Canatech - Viet Nam
- Size Range : DN15 - DN600
- Standard : BS 4504 PN10, PN16
- Number of holes : 4 - 20 holes
- Thickness : 12 - 52 (mm)

Accessories

1

Fuel Tank - TCVN



- Brand : CANATECH - Viet Nam
- Model : CA-FUVN
- Capacity : 50 - 200 Liter
- Type : Horizontal
- Material : Steel
- Finish Color : Red

2

Fuel Tank - NFPA



- Brand : CANATECH - Malaysia
- Model : CA-FUNFPA
- Capacity : 200 - 500 Liter
- Type : Horizontal
- Material : Steel
- Finish Color : Red

3

Pressure Tank



- Brand : CANATECH - Malaysia
- Model : CA50L, CA100L, CA150L, CA200L
- Capacity : 50 - 200 Liter
- Type : Vertical
- Working Pressure: Max. 16bar
- Material : Steel 5m
- Finish Color : Red

110 Cartier Cres, Hamilton Ontario, Canada, L8W-3T8
Tel: +905-920-5812 . Email: canatechfire@gmail.com

Safety for your life

